



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : SikaTack® Panel Primer

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika d.o.o.  
Prevale 13  
1236 Trzin  
Telephone : +386 1 580 95 34  
E-mail address of person : EHS@si.sika.com  
responsible for the SDS

### 1.4 Emergency telephone number

112

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements	H225	Highly flammable liquid and vapour.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.

Supplemental Hazard Statements	: EUH066	Repeated exposure may cause skin dryness or cracking.
--------------------------------	----------	---



- Precautionary statements : **Prevention:**
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - P233 Keep container tightly closed.
  - P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
  - P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
- Response:**
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
  - P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Hazardous components which must be listed on the label:**

ethyl acetate

**Additional Labelling**

EUH208 Contains dibutyltin dilaurate. May produce an allergic reaction.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

---

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Components**

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 01-2119475103-46-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 60 - < 80



xylene Contains: ethylbenzene <= 25 %	1330-20-7 215-535-7 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 5 - < 10
methanol	67-56-1 200-659-6 01-2119433307-44-XXXX	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370  specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 %	< 1
dibutyltin dilaurate	77-58-7 201-039-8 01-2119496068-27-XXXX	Skin Corr. 1C; H314 Skin Sens. 1; H317 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,025 - < 0,25

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.



- Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Excessive lachrymation  
Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
- Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : No hazardous combustion products are known



### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

---



- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU
		Further information: Indicative		
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
		MV	200 ppm 734 mg/m <sup>3</sup>	SI OEL
		Further information: Maximum level set by Commission Directive 2017/164 / EU of 31 January 2017 establishing a fourth list of indicative occupational exposure limit values in accordance with Council Directive 98/24/ EC and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU (OJ L, No 27, 1 February 2017, p. 115)., Substances without teratogenic effects when respecting limit values and bat values.		
		KTV	400 ppm 1.468 mg/m <sup>3</sup>	SI OEL
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		MV	50 ppm 221 mg/m <sup>3</sup>	SI OEL
		Further information: The properties of easier transport of substances into organism through (via) the skin		
		KTV	100 ppm 442 mg/m <sup>3</sup>	SI OEL
methanol	67-56-1	TWA	200 ppm	2006/15/EC



			260 mg/m <sup>3</sup>	
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		MV	200 ppm 260 mg/m <sup>3</sup>	SI OEL
	Further information: Maximum level set by Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC, amending Commission Directive 91/322/EEC and Commission Directive 2000/39/EC (OJ L, no. 38, dated 9 February 2006, p. 36)., The properties of easier transport of substances into organism through (via) the skin, Biological limit value - the biological limit value is set, which means a warning level of dangerous chemical substance and its metabolites in the cell tissues, body liquids or expired air, not depending on the route of entering the body, inhalation, oral or dermal, Substances without teratogenic effects when respecting limit values and bat values.			
		KTV	800 ppm 1.040 mg/m <sup>3</sup>	SI OEL

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2 g/l (Urine)	End of shift	SI BAT
methanol	67-56-1	Methanol: 30 mg/l (Urine)	during long-term exposure: at the end of the work shift after several consecutive workdays, End of shift	SI BAT

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
methanol	Workers	Skin contact		40 mg/m <sup>3</sup>
Remarks:	Exposure time: 8 h			
	Consumers	Skin contact		260 mg/m <sup>3</sup>
Remarks:	Exposure time: 8 h			

## 8.2 Exposure controls

### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:



- Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Vir za Slovenijo: Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 –ZVZD-1, 38/15 in 78/18)

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid  
Colour : black  
Odour : ester-like  
Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available  
Boiling point/boiling range : No data available
- Flash point : -4 °C  
Method: closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available





---

Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	99,9915 hPa
Relative vapour density	:	No data available
Density	:	ca. 1 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	427 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.



### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

##### xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rabbit): 1.700 mg/kg

##### methanol:

Acute inhalation toxicity : LC50: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Converted acute toxicity point estimate

##### dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat): 2.071 mg/kg

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

---



**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**11.2 Information on other hazards**

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Components:**

**xylene:**

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2 mg/l  
Exposure time: 73 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: Daphnia (water flea)

**dibutyltin dilaurate:**

Toxicity to fish : LC50 (Fish): 3,1 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l  
Exposure time: 72 h



M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

**Product:**

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

---



Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances
Nacionalni predpisi glede odpadkov	:	Uredba o odpadkih Uredba o ravnanju z embalažo in odpadno embalažo

---

## SECTION 14: Transport information

### 14.1 UN number

ADR	:	UN 1866
IMDG	:	UN 1866
IATA	:	UN 1866

### 14.2 UN proper shipping name

ADR	:	RESIN SOLUTION
IMDG	:	RESIN SOLUTION
IATA	:	Resin solution

### 14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
IATA	:	3

### 14.4 Packing group

<b>ADR</b>	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Tunnel restriction code	: (D/E)
<b>IMDG</b>	
Packing group	: II
Labels	: 3
EmS Code	: F-E, S-E
<b>IATA (Cargo)</b>	
Packing instruction (cargo aircraft)	: 364
Packing instruction (LQ)	: Y341
Packing group	: II
Labels	: Flammable Liquids
<b>IATA (Passenger)</b>	
Packing instruction (passenger aircraft)	: 353



Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

#### 14.5 Environmental hazards

##### ADR

Environmentally hazardous : no

##### IMDG

Marine pollutant : no

##### IATA (Passenger)

Environmentally hazardous : no

##### IATA (Cargo)

Environmentally hazardous : no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : dibutyltin dilaurate

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.



Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 67,75 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 67,95 %

**Other regulations:**

Chemicals Act  
Environment Protection Act  
Decree on waste  
Decree on the management of packaging and packaging waste  
Rules on the protection of workers from the risks related to exposure to chemical substances at work (Official Gazette of RS, no. 100/01, 39/05, 53/07, 102/10, 43/11 -- ZVZD-1, 38/15, 78/18 and 78/19)  
Rules on personal protective equipment used by workers at work  
Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

**15.2 Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

**SECTION 16: Other information**

**Full text of H-Statements**

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H301 : Toxic if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H311 : Toxic in contact with skin.  
H312 : Harmful in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H331 : Toxic if inhaled.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H341 : Suspected of causing genetic defects.  
H360FD : May damage fertility. May damage the unborn child.  
H370 : Causes damage to organs.  
H370 : Causes damage to organs if swallowed.  
H372 : Causes damage to organs through prolonged or repeated exposure if swallowed.  
H373 : May cause damage to organs through prolonged or repeated



- H400 : exposure if inhaled.  
H410 : Very toxic to aquatic life.  
H412 : Very toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

- Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Muta. : Germ cell mutagenicity  
Repr. : Reproductive toxicity  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2006/15/EC : Europe. Indicative occupational exposure limit values  
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values  
SI BAT : Slovenia. BAT-values  
SI OEL : Slovenia. Chemical agents at work - Appendix 1: Occupational exposure limits  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2006/15/EC / TWA : Limit Value - eight hours  
2017/164/EU / STEL : Short term exposure limit  
2017/164/EU / TWA : Limit Value - eight hours  
SI OEL / MV : Time Weighted Average  
SI OEL / KTV : Short Term Exposure Limit  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament





and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

**Further information**

**Classification of the mixture:**

Flam. Liq. 2                    H225  
Eye Irrit. 2                    H319  
STOT SE 3                    H336

**Classification procedure:**

Based on product data or assessment  
Calculation method  
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

SI / EN